

### CONSTRUCTION DATA

<b>Conductor:</b>	
# of Conductors	2
AWG	12
Conductor Stranding	19x25
Copper Type	Bare

<b>Insulation:</b>	
Type	Plenum PVC
Thickness	0.012 in.
Color Code	BK, RD

<b>Shield:</b>	
Shield Type	N/A
Drain Wire Type	N/A

<b>Jacket:</b>	
Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.263 in.
Colors	BK, GY

### Applications

* Audio
* Control
* Low Voltage Power

### X-Reference

WPW	25227B, *227
Belden	6000UE

### Water Otter Versions

Water Blocked - WB2C12GY
Direct Burial - DB2C12BK

### Cable Print

Provideon Wire & Cable #2C12PBK 2/12  
Unshielded CL2P Audio Cable A B C D E  
F G H I J 1 2 3 4 5 6 7 8 9 0 Date Code

### TECHNICAL DATA

Voltage Rating	150 V
Operating Temperature	0 to 75 C
Flame Test	NFPA 262 Plenum
NEC Rating	CL2P
RoHS Compliant	Yes
Max. Pull Tension	146 lbs
Max. Bend Radius	2.367 in
Cable Weight	54 lbs
Nominal DCR	1.7 Ohms/1000 Ft.
Nominal Cap. Between Conductors	36 pf/ft
Nominal Cap. Cond. To Shield	N/A