

CONSTRUCTION DATA

Conductor:	
# of Conductors	2
AWG	16
Conductor Stranding	19x29
Copper Type	Bare

Insulation:	
Type	Plenum PVC
Thickness	0.008 in.
Color Code	BK, RD

Shield:	
Shield Type	N/A
Drain Wire Type	N/A

Jacket:	
Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.176 in.
Colors	BK, GY, GN, SGN, WH

Applications

* Audio
* Control
* Low Voltage Power

X-Reference

WPW	25225B, *225
Belden	6200UE

Water Otter Versions

Water Blocked - WB2C16GY
Direct Burial - DB2C16BK

Cable Print

Provideon Wire & Cable #2C16PBK 2/16 Unshielded CMP Audio Cable A B C D E F G H I J 1 2 3 4 5 6 7 8 9 0 Date Code

TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	0 to 75 C
Flame Test	NFPA 262 Plenum
NEC Rating	CMP
RoHS Compliant	Yes
Max. Pull Tension	54 lbs
Max. Bend Radius	1.583 in
Cable Weight	25 lbs
Nominal DCR	4.2 Ohms/1000 Ft.
Nominal Cap. Between Conductors	36.5 pf/ft
Nominal Cap. Cond. To Shield	N/A