

CONSTRUCTION DATA

Conductor:

# of Conductors	4
AWG	20
Conductor Stranding	7x28
Copper Type	Bare

Insulation:

Type	Plenum PVC
Thickness	0.008
Color Code	(BK, RD Shld) WH, GN

Shield:

Shield Type	2 SH / 2 UNSH
Drain Wire Type	Tinned Copper

Jacket:

Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.180 in.
Colors	BK

Applications

* Audio
* Control
* Low Voltage Power

X-Reference

WPW	25359B, *359
Belden	6402GE

Water Otter Versions

Water Blocked - WB2C1P20SGY
Direct Burial - Call Engineering

Cable Print

Provideon Wire & Cable #2C1PS20PBK
4/22 Shielded CMP Audio Cable A B C D
F G H I J 1 2 3 4 5 6 7 8 9 0 Date Code

TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	0 to 60 C
Flame Test	NFPA 262 Plenum
NEC Rating	CMP
RoHS Compliant	Yes
Max. Pull Tension	63 lbs
Max. Bend Radius	1.619 in
Cable Weight	25 lbs
Nominal DCR	10.1 Ohms/1000 Ft.
Nominal Cap. Between Conductors	60 pf/ft
Nominal Cap. Cond. To Shield	108 pf/ft