

CONSTRUCTION DATA

Conductor:	
# of Conductors	6
AWG	22
Conductor Stranding	7x30
Copper Type	Bare

Insulation:	
Type	Plenum PVC
Thickness	0.007 in.
Color Code	BK, RD, WH, GN, BN, BL

Shield:	
Shield Type	Overall 100% AL Foil
Drain Wire Type	Tinned Copper

Jacket:	
Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.157 in.
Colors	BK

Applications

* Audio
* Control
* Low Voltage Power

Water Otter Versions

Water Blocked - Call Engineering
Direct Burial - Call Engineering

Cable Print

Provideon Wire & Cable #3P22PSBK 6/22 Shielded CMP Audio Cable A B C D E F G H I J 1 2 3 4 5 6 7 8 9 0 Date Code
--

TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	0 to 60 C
Flame Test	NFPA 262 Plenum
NEC Rating	CMP
RoHS Compliant	Yes
Max. Pull Tension	54 lbs
Max. Bend Radius	1.413 in.
Cable Weight	25 lbs
Nominal DCR	17 Ohms/1000 Ft.
Nominal Cap. Between Conductors	54 pf/ft
Nominal Cap. Cond. To Shield	97 pf/ft