

### CONSTRUCTION DATA

#### Conductor:

# of Conductors	4
AWG	18
Conductor Stranding	7x26
Copper Type	Bare

#### Insulation:

Type	Plenum PVC
Thickness	0.008 in.
Color Code	BK, RD, WH, GN

#### Shield:

Shield Type	N/A
Drain Wire Type	N/A

#### Jacket:

Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.180 in.
Colors	BK, WH

### Applications

* Audio
* Control
* Low Voltage Power

### X-Reference

WPW	25244B, *244
Belden	6302UE

### Water Otter Versions

Water Blocked - WB4C18GY
Direct Burial - DB4C18BK

### Cable Print

Provideon Wire & Cable #4C18PBK 4/18  
Unshielded CMP Audio Cable A B C D E F  
G H I J 1 2 3 4 5 6 7 8 9 0 Date Code

### TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	0 to 60 C
Flame Test	NFPA 262 Plenum
NEC Rating	CMP
RoHS Compliant	Yes
Max. Pull Tension	80 lbs
Max. Bend Radius	1.61 in.
Cable Weight	32 lbs
Nominal DCR	6.2 Ohms/1000 Ft.
Nominal Cap. Between Conductors	68 pf/ft
Nominal Cap. Cond. To Shield	N/A