

CONSTRUCTION DATA

Conductor:

# of Conductors	4
AWG	22
Conductor Stranding	7x30
Copper Type	Bare

Insulation:

Type	Plenum PVC
Thickness	0.007 in.
Color Code	BK, RD, WH, GN

Shield:

Shield Type	N/A
Drain Wire Type	N/A

Jacket:

Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.136 in.
Colors	BK, WH

Applications

* Audio
* Control
* Low Voltage Power

X-Reference

WPW	25241B, *241
Belden	6502UE

Water Otter Versions

Water Blocked - Call Engineering
Direct Burial - Call Engineering

Cable Print

Provideon Wire & Cable #4C22PBK 4/22
Unshielded CMP Audio Cable A B C D E F
G H I J 1 2 3 4 5 6 7 8 9 0 Date Code

TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	0 to 60 C
Flame Test	NFPA 262 Plenum
NEC Rating	CMP
RoHS Compliant	Yes
Max. Pull Tension	29 lbs
Max. Bend Radius	1.22 in.
Cable Weight	17 lbs
Nominal DCR	16.1 Ohms/1000 Ft.
Nominal Cap. Between Conductors	27 pf/ft
Nominal Cap. Cond. To Shield	N/A