

CONSTRUCTION DATA

Conductor:

# of Conductors	4
AWG	22
Conductor Stranding	7x30
Copper Type	Bare

Insulation:

Type	Plenum PVC
Thickness	0.007 in.
Color Code	BK, RD, WH, GN

Shield:

Shield Type	Overall 100% AL Foil
Drain Wire Type	Tinned Copper

Jacket:

Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.141 in.
Colors	BK, WH

Applications

* Audio
* Control
* Low Voltage Power

X-Reference

WPW	253241B, *3241
Belden	6502FE

Water Otter Versions

Water Blocked - Call Engineering
Direct Burial - Call Engineering

Cable Print

Provideon Wire & Cable #4C22PSWH 4/22
Shielded CMP Audio Cable A B C D E F G
H I J 1 2 3 4 5 6 7 8 9 0 Date Code

TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	0 to 60 C
Flame Test	NFPA 262 Plenum
NEC Rating	CMP
RoHS Compliant	Yes
Max. Pull Tension	42 lbs
Max. Bend Radius	1.269 in.
Cable Weight	18 lbs
Nominal DCR	17 Ohms/1000 Ft.
Nominal Cap. Between Conductors	54 pf/ft
Nominal Cap. Cond. To Shield	97 pf/ft