

CONSTRUCTION DATA

Conductor:	
# of Conductors	4
AWG	22
Conductor Stranding	Solid
Copper Type	Bare

Insulation:	
Type	Plenum PVC
Thickness	0.008 in.
Color Code	BK, RD, WH, GN

Shield:	
Shield Type	N/A
Drain Wire Type	N/A

Jacket:	
Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.136 in.
Colors	BK, WH

Applications

* Audio
* Control
* Low Voltage Power

X-Reference

WPW	25240B, *240
Belden	6522UE

Water Otter Versions

Water Blocked - WB4C22SBK
Direct Burial - Call Engineering

Cable Print

Provideon Wire & Cable #4C22SPBK 4/22 Unshielded CMP Audio Cable A B C D E F G H I J 1 2 3 4 5 6 7 8 9 0 Date Code
--

TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	0 to 60 C
Flame Test	NFPA 262 Plenum
NEC Rating	CMP
RoHS Compliant	Yes
Max. Pull Tension	34 lbs
Max. Bend Radius	1.206 in.
Cable Weight	17 lbs
Nominal DCR	17.5 Ohms/1000 Ft.
Nominal Cap. Between Conductors	25 pf/ft
Nominal Cap. Cond. To Shield	N/A