

### CONSTRUCTION DATA

<b>Conductor:</b>	
# of Conductors	6
AWG	22
Conductor Stranding	7x30
Copper Type	Bare

<b>Insulation:</b>	
Type	Plenum PVC
Thickness	0.007 in.
Color Code	BK, RD, WH, GN, BN, BL

<b>Shield:</b>	
Shield Type	N/A
Drain Wire Type	N/A

<b>Jacket:</b>	
Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.157 in.
Colors	BK

### Applications

* Audio
* Control
* Low Voltage Power

### X-Reference

WPW	25270B, *270
Belden	6504UE

### Water Otter Versions

Water Blocked - Call Engineering
Direct Burial - Call Engineering

### Cable Print

Provideon Wire & Cable #6C22PBK 6/22 Unshielded CMP Audio Cable A B C D E F G H I J 1 2 3 4 5 6 7 8 9 0 Date Code
---

### TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	0 to 60 C
Flame Test	NFPA 262 Plenum
NEC Rating	CMP
RoHS Compliant	Yes
Max. Pull Tension	54 lbs
Max. Bend Radius	1.413 in.
Cable Weight	25 lbs
Nominal DCR	17 Ohms/1000 Ft.
Nominal Cap. Between Conductors	27 pf/ft
Nominal Cap. Cond. To Shield	N/A