

### CONSTRUCTION DATA

#### Conductor:

# of Conductors	2
AWG	14
Conductor Stranding	19x27
Copper Type	Bare

#### Insulation:

Type	PVC/Nylon
Thickness	0.020 in.
Color Code	BK, RD

#### Shield:

Shield Type	WO Tape
Drain Wire Type	N/A

#### Jacket:

Jacket Type	UV Resistant PVC
Thickness	0.040 in.
Nominal Cable O.D.	0.310 in.
Colors	BK

### Applications

* Indoor & Outdoor Audio
* Control
* Low Voltage
* Fire Alarm

### X-Reference

WPW	AQ226
Belden	5140U1

### Water Otter Versions

Water Blocked - WB2C14GY
--------------------------

### Cable Print

Provideon Wire & Cable #DB2C14BK 2/14  
Unshielded FPL CL3 PLTC Water Otter A  
B C D E F G H I J 1 2 3 4 5 6 7 8 9 0 Date  
Code

### TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	-20 to 90 C
Flame Test	UL 1685
NEC Rating	CL3, FPL, PLTC
RoHS Compliant	Yes
Max. Pull Tension	84 lbs
Max. Bend Radius	2.79 in.
Cable Weight	59 lbs
Nominal DCR	2.7 Ohms/1000 Ft.
Nominal Cap. Between Conductors	32 pf/ft
Nominal Cap. Cond. To Shield	N/A