

CONSTRUCTION DATA

Conductor:

# of Conductors	2
AWG	14
Conductor Stranding	19x27
Copper Type	Bare

Insulation:

Type	PVC
Thickness	0.010 in.
Color Code	BK, RD

Shield:

Shield Type	WO Tape
Drain Wire Type	N/A

Jacket:

Jacket Type	UV Resistant PVC
Thickness	0.025 in.
Nominal Cable O.D.	0.294 in.
Colors	GY

Applications

* Indoor & Outdoor Audio
* Control
* Low Voltage
* Fire Alarm

X-Reference

WPW	AQC226
Belden	5140U1

Water Otter Versions

Direct Burial - DB2C14BK

Cable Print

Provideon Wire & Cable #WB2C14GY 2/14
Unshielded FPL CL3 Water Otter A B C D
E F G H I J 1 2 3 4 5 6 7 8 9 0 Date Code

TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	-20 to 90 C
Flame Test	UL 1685
NEC Rating	CL3, FPL
RoHS Compliant	Yes
Max. Pull Tension	82 lbs
Max. Bend Radius	2.646 in.
Cable Weight	48 lbs
Nominal DCR	2.7 Ohms/1000 Ft.
Nominal Cap. Between Conductors	34 pf/ft
Nominal Cap. Cond. To Shield	N/A