

### CONSTRUCTION DATA

#### Conductor:

# of Conductors	4
AWG	22
Conductor Stranding	Solid
Copper Type	Bare

#### Insulation:

Type	PVC
Thickness	0.008 in.
Color Code	BK, RD, WH, GN

#### Shield:

Shield Type	WO Tape
Drain Wire Type	N/A

#### Jacket:

Jacket Type	UV Resistant PVC
Thickness	0.025 in.
Nominal Cable O.D.	0.194 in.
Colors	GY

### Applications

* Indoor & Outdoor Audio
* Control
* Low Voltage
* Fire Alarm

### X-Reference

WPW	AQC240
-----	--------

### Water Otter Versions

Direct Burial - Call Engineering
----------------------------------

### Cable Print

Provideon Wire & Cable #WB4CS22SGY 4/22 Unshielded CM CL3 Water Otter A B C D E F G H I J 1 2 3 4 5 6 7 8 9 0 Date Code
--

### TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	-20 to 90 C
Flame Test	UL 1685
NEC Rating	CM, CL3
RoHS Compliant	Yes
Max. Pull Tension	50 lbs
Max. Bend Radius	1.862 in.
Cable Weight	43 lbs
Nominal DCR	17.5 Ohms/1000 Ft.
Nominal Cap. Between Conductors	25 pf/ft
Nominal Cap. Cond. To Shield	N/A